

有关照相机设定限制的信息

下表列出了每种拍摄模式下的可用选项。某些选项可能不适用于在特定模式下支持的项目，且根据拍摄环境的不同，功能可能会被限制。

拍摄模式/场景定位		P	S	A	M	Q ₆	BKT	■	Adv	■	■	■
闪光灯功能设置 ⁸	TTL模式	TTL Auto	✓				✓ ⁶	✓ ⁶	✓ ³	✓ ³		✓ ³
	TTL模式	TTL	✓	✓ ¹	✓	✓ ¹	✓ ⁶	✓ ⁶	✓	✓		✓
	TTL模式	TTL Slow	✓		✓		✓ ⁶	✓ ⁶	✓ ³	✓ ³		✓ ³
	同步模式	Front	✓	✓	✓	✓	✓ ⁶	✓ ⁶	✓	✓		✓
	同步模式	Rear	✓	✓	✓	✓	✓ ⁶	✓ ⁶	✓	✓		✓
	M	M	✓	✓	✓	✓	✓ ⁶	✓ ⁶	✓	✓		✓
	M	EC	✓	✓	✓	✓	✓ ⁶	✓ ⁶	✓	✓		✓
	M	Off	✓	✓	✓	✓	✓ ¹	✓	✓	✓	✓ ¹	✓
红眼修正 ⁸	闪光灯+移除	✓ ³	✓ ³	✓ ³	✓ ³							
	闪光灯	✓ ³	✓ ³	✓ ³	✓ ³							
	移除	✓ ³	✓ ³	✓ ³	✓ ³							
	关	✓	✓	✓	✓							✓ ¹
闪光补偿		✓	✓	✓	✓			✓	✓			✓ ⁷
自拍		✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
曝光补偿		✓	✓	✓	✓ ⁵	✓	✓	✓	✓	✓	✓	✓ ²
F		✓ ¹	✓ ¹	✓	✓	✓	✓	✓	✓	✓	✓	✓
S.S.		✓ ¹	✓ ⁴	✓ ¹	✓ ⁴	✓	✓	✓	✓	✓	✓ ³	✓ ³
快门类型	MS (至 1/4000)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹	✓ ⁷
	MS+ES	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓ ⁷
	ES (至 1/32000)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹	✓ ⁷
程序切换		✓				✓	✓	✓	✓	✓		✓ ⁷
AE/AF-LOCK按钮	仅 AF-LOCK	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓ ⁷
	仅 AE-LOCK	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓ ⁷
	AE/AF-LOCK	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓ ⁷
感光度	自动								✓		✓	
	自动1	✓	✓	✓	✓	✓		✓		✓		✓ ⁷
	自动2	✓	✓	✓	✓	✓		✓		✓		✓ ⁷
	自动3	✓	✓	✓	✓	✓		✓		✓		✓ ⁷
	H (51200)/H (25600)	✓	✓	✓	✓	✓	✓	✓ ³	✓			✓
	12800	✓	✓	✓	✓	✓	✓	✓ ³	✓		✓	✓
	6400 - 1000	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓
	800	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	640 - 200	✓	✓	✓	✓	✓	✓	✓ ³	✓	✓	✓	✓
	L (100)	✓	✓	✓	✓	✓	✓	✓ ³	✓			✓
图像尺寸	L	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ⁷
	M	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ⁷
	S	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ⁷
图像质量	FINE/NORMAL	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ⁷
	RAW	✓	✓	✓	✓	✓	✓	✓				✓ ⁷
RAW录制	未压缩	✓	✓	✓	✓	✓	✓	✓				✓ ⁷
	无损压缩	✓	✓	✓	✓	✓	✓	✓				✓ ⁷
动态范围	自动	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹
	±100/±200/±400	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ⁷
胶片模拟	STD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	V _R /S _R /C _R	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	N _R /N _G	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	A _R /A _G /A _B	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	B _R /B _G /B _B	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	SP _R	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
灰度效果		✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
白平衡		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
数码远摄增距镜 (50mm/70mm)		✓	✓	✓	✓	✓						
转换镜头 (广角/远摄)		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
面部识别		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
眼检测AF		✓	✓	✓	✓	✓	✓	✓	✓	✓		
测光	[○]	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ⁷
	[◎]	✓	✓	✓	✓	✓	✓	✓	✓			✓ ⁷
	[•]	✓	✓	✓	✓	✓	✓	✓	✓			✓ ⁷
	[]	✓	✓	✓	✓	✓	✓	✓	✓			✓ ⁷
对焦模式	S	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ⁷
	C	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓ ⁷
	M	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓ ⁷
自动对焦模式	[]	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹
	[□]	✓	✓	✓	✓	✓	✓	✓	✓	✓		
	[■]	✓	✓	✓	✓	✓	✓	✓	✓	✓		
摄像自动对焦模式	[+]										✓	
	[○]										✓	
手动聚焦助手	标准	✓	✓	✓	✓	✓	✓	✓	✓ ¹	✓ ¹		
	数码分割图像	✓	✓	✓	✓	✓	✓	✓				
	峰值对焦高光	✓	✓	✓	✓	✓	✓	✓				
重点AE和聚光区域互锁		✓	✓	✓	✓	✓	✓	✓	✓			✓ ⁷
AF+MF		✓	✓	✓	✓	✓	✓	✓	✓			
AF辅助灯		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ⁷
色彩		✓	✓	✓	✓	✓	✓	✓	✓			✓ ⁷
锐度		✓	✓	✓	✓	✓	✓	✓	✓			✓ ⁷
高光色调		✓	✓	✓	✓	✓						

拍摄模式/场景定位		P	S	A	M	Q ₁	BKT	■	Adv	■	■	■
显示自定义设置	取景框	✓	✓	✓	✓	✓	✓	✓	✓			
	电子水平仪	✓	✓	✓	✓	✓	✓	✓	✓		✓	
	自动对焦框	✓	✓	✓	✓	✓	✓	✓	✓			
	自动对焦距离指示	✓	✓	✓	✓	✓	✓	✓	✓			
	手动对焦距离指示	✓	✓	✓	✓	✓	✓	✓	✓		✓	
	直方图	✓	✓	✓	✓	✓	✓	✓	✓			
	选项	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	光圈/快门速度/ISO	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	信息显示背景	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	曝光补偿(数字)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	曝光补偿(标尺)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	对焦模式	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	测光	✓	✓	✓	✓	✓	✓	✓	✓			
	快门类型	✓	✓	✓	✓	✓	✓	✓	✓			
	闪光灯	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	连拍模式	✓	✓	✓	✓	✓	✓	✓				
	白平衡	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	胶片模拟	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	动态范围	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	剩余张数	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	图像大小/质量	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
显示自定义设置 (接上页)	摄像模式和拍摄时间	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	数码远摄增距镜	✓	✓	✓	✓							
	转换镜头	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	电池电量	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	框架轮廓 ¹³	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
色彩空间		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹²	✓ ⁷

¹ 自动固定。² 动画录制期间限制在 ±2.0EV 范围内。³ 可用选项根据拍摄模式的不同而异。⁴ A 不可用。⁵ 仅适用于自动 ISO 感光度。⁶ 仅适用于支持连拍模式的选购闪光灯组件。不适用于内置闪光灯。⁷ 使用了静态拍摄设定。⁸ 闪光灯无法与电子快门一起使用。当 红眼修正 选为 关 以外的选项且 脸部识别 处于开启状态时可用。⁹ 无线遥控拍摄。¹⁰ 仅当对焦模式选为 AF-S 且 自动对焦模式 选为 单点 时可用。¹¹ 在间隔定时拍摄过程中自动禁用。¹² 自动选择 sRGB。¹³ 仅在 LCD/EVF 显示中可用。