

Restrictions on Camera Settings

The options available in each shooting mode are listed below. Some options may not be available for the items that are supported in any given mode, and function may be restricted depending on shooting conditions.

Shooting mode/scene position		P	S	A	M		BKT					
FLASH FUNCTION SETTING ⁸	TTL MODE		✓				✓ ⁶	✓ ⁶	✓ ³	✓ ³		✓ ³
		✓	✓ ¹	✓	✓ ¹	✓ ⁶	✓ ⁶	✓	✓			✓
		✓		✓		✓ ⁶	✓ ⁶	✓ ³	✓ ³			✓ ³
	SYNC. MODE		✓	✓	✓	✓	✓ ⁶	✓ ⁶	✓	✓		✓
		✓	✓	✓	✓	✓ ⁶	✓ ⁶	✓	✓			✓
	M	✓	✓	✓	✓	✓ ⁶	✓ ⁶	✓	✓			✓
		✓	✓	✓	✓	✓ ⁶	✓ ⁶	✓	✓			✓
		✓	✓	✓	✓	✓ ¹	✓	✓	✓	✓ ¹		✓
RED EYE REMOVAL ⁸		✓ ³	✓ ³	✓ ³	✓ ³							
		✓ ³	✓ ³	✓ ³	✓ ³							
		✓ ³	✓ ³	✓ ³	✓ ³							
	OFF	✓	✓	✓	✓							✓ ¹
	FLASH COMPENSATION	✓	✓	✓	✓			✓	✓			✓ ²
SHUTTER TYPE	SELF-TIMER	✓	✓	✓	✓	✓	✓	✓	✓			✓
	EXP. COMPENSATION	✓	✓	✓	✓ ⁵	✓	✓	✓	✓	✓	✓	✓
	F	✓ ¹	✓ ¹	✓	✓	✓	✓	✓	✓	✓	✓	✓
	S.S.	✓ ¹	✓ ⁴	✓ ¹	✓ ⁴	✓	✓	✓	✓	✓ ³	✓ ³	✓
	MS (to 1/4,000)	✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹		✓ ¹
AE/AF-LOCK BUTTON	MS+ES	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
	ES (to 1/32,000)	✓	✓	✓	✓	✓	✓	✓	✓		✓ ¹	✓ ²
	Program shift	✓				✓	✓	✓	✓			✓ ¹
Sensitivity	AF LOCK ONLY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
	AE LOCK ONLY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
	AE/AF LOCK	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
	AUTO								✓			✓
	AUTO1	✓	✓	✓	✓	✓	✓	✓				✓ ²
	AUTO2	✓	✓	✓	✓	✓	✓	✓				✓ ²
	AUTO3	✓	✓	✓	✓	✓	✓	✓				✓ ²
	H (51200)/H (25600)	✓	✓	✓	✓	✓	✓	✓ ³	✓			✓
IMAGE SIZE	12800	✓	✓	✓	✓	✓	✓	✓ ³	✓			✓
	6400 – 1000	✓	✓	✓	✓	✓	✓	✓	✓			✓
	800	✓	✓	✓	✓	✓	✓	✓	✓			✓
	640 – 200	✓	✓	✓	✓	✓	✓	✓ ³	✓			✓
	L (100)	✓	✓	✓	✓	✓	✓	✓ ³	✓			✓
IMAGE QUALITY		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
RAW RECORDING	FINE/NORMAL	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
	RAW	✓	✓	✓	✓	✓	✓	✓				✓ ²
DYNAMIC RANGE	UNCOMPRESSED	✓	✓	✓	✓	✓	✓	✓				✓ ²
	LOSSLESS COMPRESSED	✓	✓	✓	✓	✓	✓	✓				✓ ²
FILM SIMULATION	AUTO	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
	#100/#200/#400	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
GRAIN EFFECT		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
WHITE BALANCE		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	WHITE BALANCE	✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹	✓	✓
DIGITAL TELE-CONV. (50mm/70mm)	DIGITAL TELE-CONV. (50mm/70mm)	✓	✓	✓	✓							
	CONVERSION LENS (WIDE/TELE)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
FACE DETECTION	EYE DETECTION AF	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	PHOTOMETRY		✓	✓	✓	✓	✓	✓	✓	✓ ¹	✓ ¹	✓ ²
Focus mode		✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
		✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
		✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
AF MODE		✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹		✓ ¹
		✓	✓	✓	✓	✓	✓	✓	✓			✓ ¹
MOVIE AF MODE		✓									✓	
		✓									✓	
MF ASSIST	STANDARD	✓	✓	✓	✓	✓	✓	✓	✓ ¹		✓ ¹	
	DIGITAL SPLIT IMAGE	✓	✓	✓	✓	✓	✓	✓				
	FOCUS PEAK HIGHLIGHT	✓	✓	✓	✓	✓	✓	✓				
INTERLOCK SPOT AE & FOCUS AREA	INTERLOCK SPOT AE & FOCUS AREA	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
	AF+MF	✓	✓	✓	✓	✓	✓	✓	✓			✓
AF ILLUMINATOR	AF ILLUMINATOR	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ²
	COLOR	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
SHARPNESS	SHARPNESS	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
	HIGHLIGHT TONE	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
SHADOW TONE	SHADOW TONE	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
	NOISE REDUCTION	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
LONG EXPOSURE NR	LONG EXPOSURE NR	✓	✓	✓	✓	✓	✓	✓	✓			✓ ²
	SELECT CUSTOM SETTING EDIT/SAVE CUSTOM SETTING	✓	✓	✓	✓	✓	✓	✓	✓			
FOCUS CHECK	PREVIEW EXP./WB IN MANUAL MODE				✓	✓	✓	✓	✓	✓	✓	✓ ²
	AF ¹¹	✓ ¹⁰										
FOCUS CHECK	MF ¹¹	✓	✓	✓	✓	✓	✓	✓	✓			

Shooting mode/scene position	P	S	A	M		BKT					
DISP. CUSTOM SETTING	FRAMING GUIDELINE	✓	✓	✓	✓	✓	✓	✓			
	ELECTRONIC LEVEL	✓	✓	✓	✓	✓	✓	✓	✓		✓
	FOCUS FRAME	✓	✓	✓	✓	✓	✓	✓	✓		
	AF DISTANCE INDICATOR	✓	✓	✓	✓	✓	✓	✓	✓		
	MF DISTANCE INDICATOR	✓	✓	✓	✓	✓	✓	✓			✓
	HISTOGRAM	✓	✓	✓	✓	✓	✓	✓			
	SHOOTING MODE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	APERTURE/S-SPEED/ISO	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	INFORMATION BACKGROUND	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Expo. Comp. (Digit)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Expo. Comp. (Scale)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	FOCUS MODE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	PHOTOMETRY	✓	✓	✓	✓	✓	✓				
	SHUTTER TYPE	✓	✓	✓	✓	✓	✓	✓	✓		
	FLASH	✓	✓	✓	✓	✓	✓	✓	✓		
	CONTINUOUS MODE	✓	✓	✓	✓	✓					
	WHITE BALANCE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	FILM SIMULATION	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	DYNAMIC RANGE	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	FRAMES REMAINING	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	IMAGE SIZE/QUALITY	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	MOVIE MODE & REC. TIME	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	DIGITAL TELE-CONV.	✓	✓	✓	✓						
	CONVERSION LENS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	BATTERY LEVEL	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	FRAMING OUTLINE ¹³	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
COLOR SPACE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ ¹²	✓ ¹¹

¹ Fixed automatically.² Restricted to range of ±2.0EV during movie recording.³ Options available vary with shooting mode.⁴ A is not available.⁵ Available only with auto ISO sensitivity.⁶ Available only with optional flash units that support burst mode. Not available with the built-in flash.⁷ Still photography settings are used.⁸ The flash can not be used with the electronic shutter. Available when an option other than OFF is selected for RED EYE REMOVAL and FACE DETECTION is on.⁹ Wireless remote photography.¹⁰ Available only when AF-S is selected for focus mode and SINGLE POINT is selected for AF MODE.¹¹ Disabled automatically during interval timer photography.¹² sRGB selected automatically.¹³ Available only in the LCD/EVF display.